

XTRACYCLE®



KIDS SEAT ADAPTER



- INSTRUCTIONS
- WARRANTY
- SAFETY PRECAUTIONS

WARRANTY

Xtracycle Kids Seat Adapters are guaranteed to be free from manufacturing defects for one (1) year from the original date of purchase. This warranty applies only to the original buyer and is not transferable. This warranty does not cover damage from use of this product outside of its intended range or that resulting from modification or neglect. It also does not cover wear and tear resulting from the normal use of the product. Please contact your Xtracycle dealer if you believe you have a warranty claim.

REAR KIDS SEAT ADAPTER INSTALLATION INSTRUCTIONS

Kids Seat Adapters are designed to attach the Yepp Maxi EasyFit to the Xtracycle FlightDeck. These adapters come in two versions - one for the forward seat position and one for the rear seat position. The rear adapter is the narrower of the two, and the adapters are always installed flat on top of the deck with the wide end towards the middle of the deck.

- 1 If your FlightDeck has already been installed, remove the bolts and set them aside. Remove the FlightDeck from the bike and flip it so that the cutout window is visible.



- 2 Cut out the window, so that the FlightDeck looks like this.



- 3 Place the rear adapter, flat side down, over the holes so that it aligns with all four. Insert the two skinnier, shorter, bolts (M5x25mm) and washers into the the two front holes and screw them in.



- 4 The two larger, longer, bolts (M6x45mm) and washers are used in the rearmost two holes, and they are secured with the provided nuts.




- 5 Once all the bolts are installed, make sure they are tightened to 4Nm. This will make sure that the adapter is secure, and help prevent the bolts from loosening.



- 6 Finish installing the FlightDeck, by fastening the front bolts (M5x45mm) and nuts. Tighten to 5-9 N-m.



- 7 Your rear kids seat adapter is now ready for use with a Yepp Maxi EasyFit.



- 8 Remove CarryAll lids.



- 9 Follow manufacturer instructions to install and secure Yepp Maxi EasyFit and you're ready to ride.



⚠ WARNING: Before your first ride, check tightness of all hardware - push and pull on all elements of Kids Seat Adapter and Yepp Maxi EasyFit to identify any loose hardware.

⚠ WARNING: Make sure the Yepp Maxi EasyFit is fully engaged with the adapter.

View the Xtracycle Owner's Manual at xtracycle.com/support for additional safety guidelines when riding with passengers or cargo.